

WING D LED

Recessed Luminaires



Images for the product family and options:



Description: Recessed mounted LED luminaire
 Light distribution: direct/indirect
 Optical system: translucent micro-prismatic PMMA diffuser
 Housing: steel
 Colour: white (RAL9003)

General data: Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP40/20
 Mechanical impact resistance: IK05
 Operating temperature range, °C: ta 0...+35

Installation: In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting frame to be ordered separately). Push-in terminal, 3x2x2.5mm2

Environment: Indoor

Application: Office, education, corridor, retail, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Wing D LED2x1750 G362 T830 MPRZ LT92	595	595	96	3244	24,5	132	80+	3000	3,60
Wing D LED2x2350 G363 T830 MPRZ LT92	595	595	96	4415	33,0	134	80+	3000	3,60
Wing D LED2x1750 G362 T840 MPRZ LT92	595	595	96	3419	24,5	139	80+	4000	3,60
Wing D LED2x2350 G363 T840 MPRZ LT92	595	595	96	4678	33,0	142	80+	4000	3,60
Wing D LED2x1750 G364 T830 MPRZ LT92 W625	622	622	96	3244	24,5	132	80+	3000	3,70
Wing D LED2x2350 G365 T830 MPRZ LT92 W625	622	622	96	4415	33,0	134	80+	3000	3,70
Wing D LED2x1750 G364 T840 MPRZ LT92 W625	622	622	96	3419	24,5	139	80+	4000	3,70
Wing D LED2x2350 G365 T840 MPRZ LT92 W625	622	622	96	4678	33,0	142	80+	4000	3,70


* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

TECHNICAL DATA SHEET

Available options:

DALI	Driver with DALI interface and switch-control dimming	1G	Strain relief for power supply cable
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)	WIE3	3-pole "Wieland - gesis classic" type or compatible connector
TW	Integrated light source and driver for Tuneable white control 2700-6500 K	WIE4	4-pole "Wieland - gesis classic" type or compatible connector
BLT TW	Integrated light source, wireless control unit and driver for Tuneable white control 2700-6500 K via mobile device (via Bluetooth)	WIE5	5-pole "Wieland - gesis classic" type or compatible connector
COR	Driver with Corridor function (never off)	WIE5D	5-pole DALI "Wieland - gesis classic" type or compatible connector
COR1min	Driver with Corridor function 1min (switch off after 1 min.)	Schuko-1.5m	3-pole "Schuko" type plug with 3x1.0mm ² 1.5m cable
COR30min	Driver with Corridor function 30min (switch off after 30 min.)	Schuko-3.0m	3-pole "Schuko" type plug with 3x1.0mm ² 3.0m cable
EM3	Emergency version 3 hours	RAL	RAL colour
EM3B	Emergency version 3 hours (best available technology)	MPRZ LT92	Translucent micro-prismatic diffuser with high light transmittance
EM3A	Emergency version equipped with an autonomous testing system, 3 hours	T830	Colour temperature 3000K, CRI 80+
EM3D	Emergency version 3 hours with DALI interface	T840	Colour temperature 4000K, CRI 80+

STANDARD



Available accessories:



Product: Recessed MTG FRAME S626x626 RAL9003
Description: Frame for LED luminaire 595x595mm
installation into plasterboard ceiling (1pcs), white steel

Applications:



