


CYGNI LED

Outdoor accent lighting



Images for the product family and options:



Description:

Surface mounted accent LED luminaire
 Light distribution type: direct
 Optical system: lenses, 30°, tempered glass diffuser, impact resistant
 Housing: aluminium
 Colour: light grey

General data:

Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP66
 Mechanical impact resistance: IK09
 Operating temperature range, °C: ta -25...+40

Installation:

On the horizontal or vertical surface (mounting bracket included). Cable, 1.0m, 3x1.5mm²

Environment:

Outdoor

Application:

Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Cygni LED1x1900 D775 T730 L30	705	82	164	1821	15,8	120	80+	3000	3,0
Cygni LED1x2400 D776 T730 L30	705	82	164	2275	22,6	105	80+	3000	3,0
Cygni LED1x3200 D777 T730 L30	705	82	164	3036	29,9	106	80+	3000	3,0
Cygni LED1x3800 D778 T730 L30	1265	82	164	3643	29,9	127	80+	3000	6,0
Cygni LED1x4800 D779 T730 L30	1265	82	164	4551	42,7	111	80+	3000	6,0
Cygni LED1x6400 D780 T730 L30	1265	82	164	6072	59,7	106	80+	3000	6,0
Cygni LED1x1900 D775 T740 L30	705	82	164	1897	15,8	120	80+	4000	3,0
Cygni LED1x2400 D776 T740 L30	705	82	164	2370	22,6	105	80+	4000	3,0
Cygni LED1x3200 D777 T740 L30	705	82	164	3162	29,9	106	80+	4000	3,0
Cygni LED1x3800 D778 T740 L30	1265	82	164	3794	29,9	127	80+	4000	6,0
Cygni LED1x4800 D779 T740 L30	1265	82	164	4740	42,7	111	80+	4000	6,0
Cygni LED1x6400 D780 T740 L30	1265	82	164	6324	59,7	106	80+	4000	6,0

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification


*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T730 Colour temperature 3000K, CRI 70+
 T740 Colour temperature 4000K, CRI 70+
 DALI Driver with DALI interface and switch-control dimming

L30 Optics with 30x30° beam angle
 1LIN 2xCBF3x0.3m Through wiring single phase d=1.5 mm² with two flexible cables 3x1.5mm². Cable lengths: 0.3m

STANDARD



Available accessories:



Product: Power supply connector - IP66/IP68, 3x1.5mm²
 Description: Quick and easy to connect power supply and luminaire cable connector - IP66/IP68, 3x1.5mm², 400V/16A, 1pcs

Applications:

