


SHARQI A LED

Spotlights



Images for the product family and options:



Description:	Recessed mounted adjustable LED spotlight Light distribution type: direct Optical system: faceted aluminium reflector, clear, PMMA diffuser Housing: aluminium Colour: white (RAL 9016), black (RAL 9017)
General data:	Mains voltage: 220-240V, 0/50/60Hz LED lifetime, h: 60000/L80B10 (T930, T940: 50000/L80B10) SDCM: 3 Protection class IEC: II Ingress protection code: IP20 Mechanical impact resistance: IK02 Operating temperature range, °C: ta 0...+35
Installation:	In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm ²
Environment:	Indoor
Application:	Retail, showroom, museum, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Sharqi A LED1x1900 G668 T830 R40 RAL9016	125	125	170	1820	13,5	135	80+	3000	0,85
Sharqi A LED1x2550 G669 T830 R40 RAL9016	125	125	170	2473	19,8	125	80+	3000	0,85
Sharqi A LED1x3350 G670 T830 R40 RAL9016	125	125	170	3329	27,1	123	80+	3000	0,85
Sharqi A LED1x1900 G668 T840 R40 RAL9016	125	125	170	1924	13,5	143	80+	4000	0,85
Sharqi A LED1x2550 G669 T840 R40 RAL9016	125	125	170	2613	19,8	132	80+	4000	0,85
Sharqi A LED1x3350 G670 T840 R40 RAL9016	125	125	170	3518	27,1	130	80+	4000	0,85
Sharqi A LED1x1900 G668 T930 R40 RAL9016	125	125	170	1543	13,3	116	90+	3000	0,85
Sharqi A LED1x2550 G669 T930 R40 RAL9016	125	125	170	2114	19,3	110	90+	3000	0,85
Sharqi A LED1x3350 G670 T930 R40 RAL9016	125	125	170	2872	26,4	109	90+	3000	0,85
Sharqi A LED1x1900 G668 T940 R40 RAL9016	125	125	170	1625	13,3	122	90+	4000	0,85
Sharqi A LED1x2550 G669 T940 R40 RAL9016	125	125	170	2228	19,3	115	90+	4000	0,85
Sharqi A LED1x3350 G670 T940 R40 RAL9016	125	125	170	3028	26,4	115	90+	4000	0,85
Sharqi A LED1x1900 G668 T830 R40 RAL9017	125	125	170	1820	13,5	135	80+	3000	0,85
Sharqi A LED1x2550 G669 T830 R40 RAL9017	125	125	170	2473	19,8	125	80+	3000	0,85
Sharqi A LED1x3350 G670 T830 R40 RAL9017	125	125	170	3329	27,1	123	80+	3000	0,85
Sharqi A LED1x1900 G668 T840 R40 RAL9017	125	125	170	1924	13,5	143	80+	4000	0,85
Sharqi A LED1x2550 G669 T840 R40 RAL9017	125	125	170	2613	19,8	132	80+	4000	0,85
Sharqi A LED1x3350 G670 T840 R40 RAL9017	125	125	170	3518	27,1	130	80+	4000	0,85
Sharqi A LED1x1900 G668 T930 R40 RAL9017	125	125	170	1543	13,3	116	90+	3000	0,85
Sharqi A LED1x2550 G669 T930 R40 RAL9017	125	125	170	2114	19,3	110	90+	3000	0,85

