
LEO LED

Outdoor Accent Lighting





Images for the product family and options:



Description:	Surface mounted accent LED luminaire Light distribution type: direct/indirect Optical system: opal polycarbonate diffuser, UV stable, impact resistant Housing: aluminium Colour: dark grey (RAL7043)
General data:	Mains voltage: 220-240V, 50/60Hz LED lifetime, h: 50000/L80B50 SDCM: 3 Protection class IEC: I Ingress protection code: IP54 Mechanical impact resistance: IK08 Operating temperature range, °C: ta -25…+40
Installation:	On the walls or ceiling. Push-in terminal, 3x2x2.5mm2
Environment:	Outdoor
Application:	Facade illumination, parking area, public space


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Leo 1E27 C402	265	265	90						1,6
Leo LED1x1200 D034 T830	265	265	90	1118	13,6	82	80+	3000	1,7
Leo LED1x1200 D034 T840	265	265	90	1173	13,6	86	80+	4000	1,7
Leo 1E27 C402 LOUVER	265	265	100						1,9
Leo LED1x1200 D034 T830 LOUVER	265	265	100	688	13,6	50	80+	3000	2
Leo LED1x1200 D034 T840 LOUVER	265	265	100	722	13,6	53	80+	4000	2

**Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification*

Available options:

T830	Colour temperature 3000K, CRI 80+	DALI	Driver with DALI interface and switch-control dimming
T840	Colour temperature 4000K, CRI 80+	RAL	RAL colour
LOUVER	Decorative louver		

STANDARD



LOUVER

