


## AUSTRU D LED

### Outdoor accent lighting



**Images for the product family and options:**



**Description:** Surface mounted accent LED luminaire  
 Light distribution type: direct  
 Optical system: lenses, 2x60°, tempered glass diffuser, impact resistant  
 Housing: aluminium  
 Colour: dark grey, RAL7043

**General data:** Mains voltage: 220-240V, 50-60Hz  
 LED lifetime, h: 40000/L70B50  
 SDCM: 5  
 Protection class IEC: I  
 Ingress protection code: IP54  
 Mechanical impact resistance: IK08  
 Operating temperature range, °C: ta -25...+40

**Installation:** On the wall. Screw terminal, 3x1x1.5 mm²


**Environment:** Outdoor

**Application:** Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Austru D LED1x600 C406 T840	125	90	80	510	6,7	77	80+	4000	0,6

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**STANDARD**



**Applications:**

