


HEZE P LED

Diffuser and Wall Luminaires



Images for the product family and options:



Description: Surface mounted plastic LED luminaire
 Light distribution type: direct
 Optical system: opal acrylic diffuser, UV resistant
 Housing: thermoplastic
 Colour: white, dark grey

General data: Mains voltage: 220-240V, 0/50-60Hz
 LED lifetime, h: 50000/L80B10
 SDCM: 3
 Protection class IEC: II
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -15...+35 (from 0 °C with EM3)

Installation: On the ceiling or wall. Push-in terminal, 2x2x2.5mm2 (Screw terminal, 2x1.5mm2 for E27 version)

Environment: Indoor/outdoor with roof

Application: Office, education, hotel, corridor, staircase, healthcare, bathroom, public place, parking area



Luminaire is available in dark grey body (DGREY). For more information see the option list.

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Heze P 1E27 Z70	295	295	90						1,4
Heze P 2E27 Z71	295	295	90						1,4
Heze P LED1x1200 D960 T830	295	295	90	1107	10,1	110,00	80+	3000	1,7
Heze P LED1x1650 D961 T830	295	295	90	1547	14,7	105,00	80+	3000	1,7
Heze P LED1x1200 D960 T840 1G	295	295	90	1167	10,1	115,00	80+	4000	1,7
Heze P LED1x1650 D961 T840 1G	295	295	90	1631	14,7	111,00	80+	4000	1,7
Heze P 1E27 Z70 DGREY	295	295	90						1,4
Heze P 2E27 Z71 DGREY	295	295	90						1,4
Heze P LED1x1200 D960 T830 DGREY	295	295	90	1107	10,1	110,00	80+	3000	1,7
Heze P LED1x1650 D961 T830 DGREY	295	295	90	1547	14,7	105,00	80+	3000	1,7
Heze P LED1x1200 D960 T840 DGREY	295	295	90	1167	10,1	115,00	80+	4000	1,7
Heze P LED1x1650 D961 T840 DGREY	295	295	90	1631	14,7	111,00	80+	4000	1,7
Heze P 1E27 Z70 LOUVER	295	295	90						1,4
Heze P 2E27 Z71 LOUVER	295	295	90						1,4
Heze P LED1x1200 D960 T830 LOUVER	295	295	90	678	10,1	67,00	80+	3000	1,7
Heze P LED1x1650 D961 T830 LOUVER	295	295	90	947	14,7	64,00	80+	3000	1,7
Heze P LED1x1200 D960 T840 LOUVER	295	295	90	715	10,1	71,00	80+	4000	1,7
Heze P LED1x1650 D961 T840 LOUVER	295	295	90	999	14,7	68,00	80+	4000	1,7
Heze P 1E27 Z70 LOUVER DGREY	295	295	90						1,4
Heze P 2E27 Z71 LOUVER DGREY	295	295	90						1,4
Heze P LED1x1200 D960 T830 LOUVER DGREY	295	295	90	678	10,1	67,00	80+	3000	1,7
Heze P LED1x1650 D961 T830 LOUVER DGREY	295	295	90	947	14,7	64,00	80+	3000	1,7
Heze P LED1x1200 D960 T840 LOUVER DGREY	295	295	90	715	10,1	71,00	80+	4000	1,7
Heze P LED1x1650 D961 T840 LOUVER DGREY	295	295	90	999	14,7	68,00	80+	4000	1,7

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830	Colour temperature 3000K, CRI 80+
T840	Colour temperature 4000K, CRI 80+
LOUVER	Decorative louver
DALI	Driver with DALI interface and switch-control dimming
MW	Integrated microwave (MW) motion sensor with on-off control
MWRFMD	Built-in microwave motion sensor with integrated wireless transceiver. Sensor can serve as both master and slave. Functions: staircase, corridor, dimming control.
MWRFM	Built-in microwave motion sensor with integrated wireless transceiver. Sensor can serve as both master and slave. Functions: staircase, corridor.

MWRFSD	Built-in wireless receiver for receiving master luminaire control signals. Functions: staircase, corridor, dimming control.
MWRFS	Built-in wireless receiver for receiving master luminaire control signals. Functions: staircase, corridor.
EM3	Emergency version 3 hours
EM3B	Emergency version 3 hours (best available technology)
EM3A	Emergency version equipped with an autonomous testing system, 3 hours
EM3D	Emergency version 3 hours with DALI interface
<i>*note - Operating temperature range for Luminaires with EM option, C: ta 0...+35</i>	
DGREY	Dark grey thermoplastic body

