

CETUS P LED

Diffuser and Wall Luminaires



220-240V
50-60Hz

IP
65

Description:

Surface mounted plastic LED luminaire
Light distribution type: direct
Optical system: opal polycarbonate diffuser, impact resistant
Housing: polycarbonate
Colour: white

General data:

Mains voltage: 220-240V, 50/60Hz
LED lifetime, h: 40000/L70B50
SDCM: 5
Protection class IEC: II
Ingress protection code: IP65
Mechanical impact resistance: IK08
Operating temperature range, °C: ta -15...+35

Installation:

On the ceiling or wall. Screw terminal, 2x1.5mm²

Environment:

Indoor

Application:

Office, education, corridor, staircase, healthcare, bathroom, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Cetus P LED1x1200 D671 T830 OP	160	160	63	1080	12	90	80+	3000	0,2

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification
*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

T830 Colour temperature 3000K, CRI 80+
OP Opal diffuser

