


ANTLIA C LED

Downlights



Description: Surface mounted LED downlight
 Light distribution type: direct
 Optical system: opal polycarbonate diffuser
 Housing: aluminium
 Colour: white (RAL9016)

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 60000/L80B10
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP44
 Mechanical impact resistance: IK04
 Operating temperature range, °C: ta 0...+35

Installation: On the ceiling. Push-in terminal, 3x2x2.5mm²

Environment: Indoor

Application: Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output ¹ , lm	System power ² , W	System efficacy ³ , lm/W	CRI	CCT ⁴ , K	Weight, kg
Antlia C LED1x1400 D345 T830 OP	200	200	130	1261	11,8	107	80+	3000	1,0
Antlia C LED1x1900 D346 T830 OP	200	200	130	1774	16	111	80+	3000	1,0
Antlia C LED1x2600 D347 T830 OP	200	200	130	2458	23,1	107	80+	3000	1,0
Antlia C LED1x1400 D345 T840 OP	200	200	130	1321	11,8	112	80+	4000	1,0
Antlia C LED1x1900 D346 T840 OP	200	200	130	1858	16	116	80+	4000	1,0
Antlia C LED1x2600 D347 T840 OP 1G	200	200	130	2575	23,1	112	80+	4000	1,0


*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- DALI Driver with DALI interface and switch-control dimming
- EM3 Emergency version 3 hours
- EM3B Emergency version 3 hours (best available technology)
- *note - EM3B options not applicable for models: D347
- SUS Suspended version
- RAL RAL colour

STANDARD



Available accessories:



Product: Suspension MTG KIT SUSI
 Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
 *note - 3pcs MTG KIT SUSI for one fitting required
 *note - SUS option is required