


AUSTRU D LED

Outdoor accent lighting



Images for the product family and options:



Description: Surface mounted accent LED luminaire
 Light distribution type: direct
 Optical system: lenses, 2x60°, tempered glass diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey, RAL7043

General data: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 40000/L70B50
 SDCM: 5
 Protection class IEC: I
 Ingress protection code: IP54
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the wall. Screw terminal, 3x1x1.5 mm²

Environment: Outdoor


Application: Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI * (Ra)	CCT*, K	Weight, kg
Austru D LED1x600 C406 T840	125	90	80	510	6,7	77	80+	4000	0,6

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

STANDARD



Applications:

