


DUBHE LED

Product Group: Outdoor accent lighting



Images for the product family and options:



Description: A surface IP54 LED luminaire with opal diffuser for outdoor wall applications
 Diffuser: opal polycarbonate, UV stable, impact resistant
 Body: die-cast aluminum, dark grey finish

General data: Mains voltage: 220-240V, 50-60Hz
 Power factor: >0,50/0,80
 Light source: 1xE27/LED
 Light source included: No/yes
 Light distribution type: Direct
 LED lifetime, h: 50000/L80B50
 Operating temperature range, °C: ta -25...+40
 Protection class IEC: I
 Ingress protection code: IP54
 Mechanical impact resistance: IK08
 EEC: A/A+

Installation: Surface mounted luminaire is designed to be fixed to walls or ceiling of any type. Push-in terminal, 3x2x2.5mm2

Environment: Outdoor

Application: Facade illumination, parking area, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Dubhe S 1E27 C420	190	190	60						1,10
Dubhe S LED1x300 C421 T830	190	190	60	215	4,0	54	80+	3000	1,20
Dubhe S 1E27 C420 LOUVER	190	190	65						1,20
Dubhe S LED1x300 C421 T830 LOUVER	190	190	65	132	4,0	33	80+	3000	1,30
Dubhe M 1E27 C423	270	270	80						1,30
Dubhe M LED1x900 D052 T830	270	270	80	798	10,0	80	80+	3000	1,40
Dubhe M LED1x900 D052 T840	270	270	80	835	10,0	83	80+	4000	1,40
Dubhe M 1E27 C423 LOUVER	270	270	85						1,50
Dubhe M LED1x500 D053 T830 LOUVER	270	270	85	430	7,3	59	80+	3000	1,60
Dubhe M LED1x500 D053 T840 LOUVER	270	270	85	451	7,3	62	80+	4000	1,60

* tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C

Available options:

DALI Driver with DALI interface
 MW MW sensor
 LOUVER Decorative louver
 RAL RAL colour
 T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+

