
WING D LED

Recessed Luminaires





Images for the product family and options:



Description:	Recessed mounted LED luminaire Light distribution: direct/indirect Optical system: translucent micro-prismatic PMMA diffuser Housing: steel Colour: white (RAL9003)
General data:	Mains voltage: 220-240V, 0/50/60Hz LED lifetime, h: 100000/L80B50 SDCM: 3 Protection class IEC: I Ingress protection code: IP40/20 Mechanical impact resistance: IK05 Operating temperature range, °C: ta 0…+35
Installation:	In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting frame to be ordered separately). Push-in terminal, 3x2x2.5mm2
Environment:	Indoor
Application:	Office, education, corridor, retail, public place


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Wing D LED2x1750 G362 T830 MPRZ LT92	595	595	96	3244	24,5	132	80+	3000	3,60
Wing D LED2x2350 G363 T830 MPRZ LT92	595	595	96	4415	33,0	134	80+	3000	3,60
Wing D LED2x1750 G362 T840 MPRZ LT92	595	595	96	3419	24,5	139	80+	4000	3,60
Wing D LED2x2350 G363 T840 MPRZ LT92	595	595	96	4678	33,0	142	80+	4000	3,60
Wing D LED2x1750 G364 T830 MPRZ LT92 W625	622	622	96	3244	24,5	132	80+	3000	3,70
Wing D LED2x2350 G365 T830 MPRZ LT92 W625	622	622	96	4415	33,0	134	80+	3000	3,70
Wing D LED2x1750 G364 T840 MPRZ LT92 W625	622	622	96	3419	24,5	139	80+	4000	3,70
Wing D LED2x2350 G365 T840 MPRZ LT92 W625	622	622	96	4678	33,0	142	80+	4000	3,70

** Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification*

Available options:

DALI	Driver with DALI interface and switch-control dimming
BLT	Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)
TW	Integrated light source and driver for Tuneable white control 2700-6500 K
BLT TW	Integrated light source, wireless control unit and driver for Tuneable white control 2700-6500 K via mobile device (via Bluetooth)
COR	Driver with Corridor function (never off)
COR1min	Driver with Corridor function 1min (switch off after 1 min.)
COR30min	Driver with Corridor function 30min (switch off after 30 min.)
EM3	Emergency version 3 hours
EM3B	Emergency version 3 hours (best available technology)
EM3A	Emergency version equipped with an autonomous testing system, 3 hours
EM3D	Emergency version 3 hours with DALI interface
1G	Strain relief for power supply cable
WIE3	3-pole "Wieland - gesis classic" type or compatible connector
WIE4	4-pole "Wieland - gesis classic" type or compatible connector
WIE5	5-pole "Wieland - gesis classic" type or compatible connector
WIE5D	5-pole DALI "Wieland - gesis classic" type or compatible connector
Schuko-1.5m	3-pole "Schuko" type plug with 3x1.0mm² 1.5m cable
Schuko-3.0m	3-pole "Schuko" type plug with 3x1.0mm² 3.0m cable
RAL	RAL colour
MPRZ LT92	Translucent micro-prismatic diffuser with high light transmittance
T830	Colour temperature 3000K, CRI 80+
T840	Colour temperature 4000K, CRI 80+

STANDARD



Available accessories:



Product: Recessed MTG FRAME S626x626 RAL9003
Description: Frame for LED luminaire 595x595mm installation into plasterboard ceiling (1pcs), white steel

Applications:




FIRE
EXIT