


# AUSTRU LED

## Outdoor Accent Lighting



**Images for the product family and options:**



**Description:** Surface mounted accent LED luminaire  
 Light distribution type: direct  
 Optical system: lenses, 2x60°, tempered glass diffuser, impact resistant  
 Housing: aluminium  
 Colour: dark grey (RAL7043)

**General data:** Mains voltage: 220-240V, 50/60Hz  
 LED lifetime, h: 40000/L70B50  
 SDCM: 5  
 Protection class IEC: I  
 Ingress protection code: IP54  
 Mechanical impact resistance: IK08  
 Operating temperature range, °C: ta -25...+40

**Installation:** On the wall. Screw terminal, 3x1x1.5mm2

**Environment:** Outdoor

**Application:** Facade illumination


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
---------	------------	-----------	------------	-----------------------	------------------	------------------------	-----	---------	------------

Austru D LED1x600 C406 T840 125 90 80 510 6,7 77 80+ 4000 0,55

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**  
 T740 Colour temperature 4000K, CRI 70+

**STANDARD**



**Applications:**

