

CURSA LED1X4300 J190 T940 R40 • 1115542



Product:	Cursa LED1x4300 J190 T940 R40		
Order code:	1115542		
Family:	Cursa LED		
Product group:	Spotlights		

GENERAL DATA

Description:	Recessed mounted adjustable LED spotlight Light distribution type: direct Optical system: faceted aluminium reflector, clear PMMA diffuser, tilting ±30°, rotatable 355° Housing: aluminium Colour: white (RAL9016)	
Instalation:	In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1.5mm2	
Environment	Indoor	
Application	retail, public place, showroom, museum, exhibition	

ELECTRICAL DATA

EEC:


Ε


Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	34
Power factor:	0.95	Control gear:	ECG on/off
Integrated sensor:	None	Surge protection (L to N), kV:	1
Surge protection (L/N to PE), kV:	2	Inrush current (Imax/time):	5A 50μsec
Overvoltage protection:	320V AC, 1h	Connection:	Push-in terminal, 2x1.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	3799	System efficacy, lm/W:	112
CRI (Ra):	90+	CCT, K:	4000
SDCM:	3	Light Distribution:	Symmetrical medium beam (3175)
Distribution Type:	Direct	Beam angle, °:	31
LED lifetime, h:	50000/L80B10	Ripple current (≤120 Hz), %:	≤3
TECHNICAL DATA			
Net weight, kg:	1.5	Mounting holes/cut-out dimensions, mm:	d170
Quantity in package, pcs:	1	Packaging volume, m3/pcs:	0.0051
Pallet quantity, pcs:	170		
Dimensions, mm:	180x180x125		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	II
Ingress protection code:	IP20	Mechanical impact resistance:	IK02

Certificates:


CE, UKCA, RoHS

Technical drawing (.jpg)





Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-05-03 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org