# NORTHCLIFFE MAKING LIFE BRIGHTER

### CETUS P LED1X1200 D671 T830 OP • 1024015



| Product:       | Cetus P LED1x1200 D671 T830 OP |
|----------------|--------------------------------|
| Order code:    | 1024015                        |
| Family:        | Cetus P LED                    |
| Product group: | Diffuser and wall luminaires   |


### GENERAL DATA

| Description: | Surface mounted plastic LED luminaire                                      |
|--------------|--|
|              | Light distribution type: direct  |
|              | Optical system: opal polycarbonate diffuser, impact resistant              |
|              | Housing: polycarbonate   |
|              | Colour: white  |
| Instalation: | On the ceiling or wall. Screw terminal, 2x1.5mm2                           |
| Environment  | : Indoor   |
| Application  | office, education, corridor, public place, staircase, bathroom, healthcare |
|              |  |


### ELECTRICAL DATA

| Mains voltage:  | 220-240V, 50/60Hz                 | System power*, W:   | 12                              |
|---|-----------------------------------|---|---------------------------------|
| Power factor:   | >0,55                             | Control gear:   | ECG on/off                      |
| Integrated sensor:  | None                              | Connection:   | Screw terminal, 2x1.5mm2        |
| LIGHTING DATA   |                                   |   |                                 |
| Light source and cap, W:  | LED                               | Light source included:  | yes                             |
| Luminaire output*,<br>lm(ta+25°C):  | 1080                              | System efficacy, lm/W:  | 90                              |
| CRI (Ra):   | 80+                               | сст, к:   | 3000                            |
| SDCM:   | 5                                 | Light Distribution:   | Symmetrical wide beam (76°125°) |
| Distribution Type:  | Direct                            | Beam angle, °:  | 126                             |
| LED lifetime, h:  | 40000/L70B50                      |   |                                 |
|   |                                   |   |                                 |
| TECHNICAL DATA  |                                   |   |                                 |
| Net weight, kg:   | 0.19                              | Quantity in package, pcs:   | 1                               |
|   | 0.19<br>0.0022                    | Quantity in package, pcs:<br>Pallet quantity, pcs:                  | 1<br>390                        |
| Net weight, kg:   |                                   |   |                                 |
| Net weight, kg:<br>Packaging volume, m3/pcs:  | 0.0022                            |   |                                 |
| Net weight, kg:<br>Packaging volume, m3/pcs:<br>Dimensions, mm:   | 0.0022                            |   |                                 |
| Net weight, kg:<br>Packaging volume, m3/pcs:<br>Dimensions, mm:<br>STANDARDS<br>Operating temperature               | 0.0022<br>160x160x63              | Pallet quantity, pcs:   | 390                             |
| Net weight, kg:<br>Packaging volume, m3/pcs:<br>Dimensions, mm:<br>STANDARDS<br>Operating temperature<br>range, °C: | 0.0022<br>160x160x63<br>ta -15+35 | Pallet quantity, pcs:<br>Protection class IEC:<br>Mechanical impact | 390<br>II                       |

Technical drawing (.jpg)



# Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-05-04 NORTHCLIFFE LIGHTING, UAB Raudondvario pl. 101, LT-47184 Kaunas, Lithuania info@northcliffe.org www.northcliffe.org