

PAVO P LED1X1100 D515 T830 • 1022736

Product:	Pavo P LED1x1100 D515 T830
Order code:	1022736
Family:	Pavo P LED
Product group:	Diffuser and wall luminaires

GENERAL DATA

Description:	Surface mounted LED luminaire Light distribution: direct Optical system: opal PMMA diffuser Housing: steel Colour: white (RAL 9003)
Installation:	On the ceiling or wall. Screw terminal, 3x1.5mm2
Environment	Indoor
Application	office, education, corridor, public place, hotel, staircase, bathroom, healthcare

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	12
Power factor:	>0,90	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Screw terminal, 3x1.5mm2

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	1020	System efficacy, lm/W:	85
CRI (Ra):	80+	CCT, K:	3000
SDCM:	5	Light Distribution:	Symmetrical wide beam (76°...125°)
Distribution Type:	Direct	Beam angle, °:	118
UGR index:	≤22	LED lifetime, h:	40000/L70B50


TECHNICAL DATA

Net weight, kg:	0.46	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0087	Pallet quantity, pcs:	100
Dimensions, mm:	280x280x90		


STANDARDS

Operating temperature range, °C:	ta -15...+35	Protection class IEC:	I
Ingress protection code:	IP44	Mechanical impact resistance:	IK02
EEC:	F	Certificates:	CE, RoHS, UKCA
Warranty:	3 years		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.