

HERMETIC R LED1x3800 D163 T840 OP LT80 • 1020709


Product:	Hermetic R LED1x3800 D163 T840 OP LT80
Order code:	1020709
Family:	Hermetic R LED
Product group:	Waterproof and cleanroom luminaires

GENERAL DATA

Description:	Recessed mounted cleanroom LED luminaire Light distribution type: direct Optical system: opal acrylic diffuser, good chemical resistance Housing: steel Colour: white (RAL9003)
Installation:	In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting brackets to be ordered separately). Push-in terminal, 3x2x2.5mm ²
Environment	Indoor
Application	industry, healthcare, laboratory

ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	32.5
Power factor:	>0,95	Control gear:	ECG on/off
Integrated sensor:	None	Surge protection (L to N), kV:	1
Surge protection (L/N to PE), kV:	2	Inrush current (I_{max}/time):	22A/ 140µs
Overvoltage protection:	330V AC, 1h	Connection:	Push-in terminal, 3x2x2.5mm ²

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	4060	System efficacy, lm/W:	125
CRI (Ra):	80+	CCT, K:	4000
SDCM:	3	Light Distribution:	Wide-wide beam (C0-C180 plane 76 ...125 , C90-C270 plane 76 ...125)
Distribution Type:	Direct	Beam angle, °:	106x106
UGR index:	≤22	LED lifetime, h:	100000/L80B10
Ripple current (≤120 Hz), %:	≤3		

TECHNICAL DATA


Net weight, kg:	4.4	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0316	Pallet quantity, pcs:	30
Dimensions, mm:	595x595x75		

STANDARDS


Operating temperature range, °C:	ta -10...+35	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK05
EEC:	D	Certificates:	CE, UKCA, RoHS

Warranty:	3 years (5 years – see warranty Ts and Cs)
-----------	---

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:	Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.
-------	---