

## **TAURUS 3HLED G07 DELUXE • 1019230**



Product:	Taurus 3HLED G07 Deluxe	
Order code:	1019230	
Family:	Taurus LED	
Product group:	Emergency lighting	


## GENERAL DATA

Description:	Surface mounted double-sided LED emergency exit sign		
	Light distribution type: omnidirectional Optical system: clear PMMA diffuser		
	Housing: extruded aluminium		
	Colour: light grey		
	Battery charging time: 24 hours		
	Battery: NiCd, deep discharge protection		
	Recognition distance: 30 meters		
Instalation:	On the ceiling or wall (mounting brackets included), or		
	suspended (requires an accessory). Push-in terminal,		
	4x2x2.5mm2		
Environment	Indoor		
Application	emergency exit sign		

## ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	1
Power factor:	>0,60	Control gear:	ECG on/off
Illumination mode:	NM	Emergency operating time, h:	3
Connection:	Push-in terminal, 4x2x2.5mm2		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
CRI (Ra):	80+	CCT, K:	6500
SDCM:	3	Light Distribution:	Other
Distribution Type:	Omnidirectional	LED lifetime, h:	50000/L80B50
TECHNICAL DATA			
Net weight, kg:	1.3	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0039	Pallet quantity, pcs:	256
Dimensions, mm:	315x48x243		
STANDARDS			
Operating temperature range, °C:	ta 0+40	Protection class IEC:	I
Ingress protection code:	IP41	Mechanical impact resistance:	IK02
Certificates:	CE, UKCA, RoHS	Warranty:	2 years

Technical drawing (.jpg)



Note:

\*: M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data:  $\pm 10\%$ , values apply to an ambient temperature of 25°C

Date of issue: 2024-05-02 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org