NORTHCLIFFE
MAKING LIFE BRIGHTER

TAURUS 1PLED G08 DELUXE TEST • 1019238



Product:	Taurus 1PLED G08 Deluxe TEST
Order code:	1019238
Family:	Taurus LED
Product group:	Emergency lighting

GENERAL DATA

Description:	Surface mounted double-sided LED emergency exit sign Light distribution type: omnidirectional Optical system: clear PMMA diffuser Housing: extruded aluminium Colour: light grey Battery charging time: 24 hours Battery: NiCd, deep discharge protection Recognition distance: 30 meters
Instalation:	On the ceiling or wall (mounting brackets included), or suspended (requires an accessory). Push-in terminal, 4x2x2.5mm2
Environment	Indoor
Application	emergency exit sign

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	**System power*, W:**	1
Power factor:	>0,60	**Control gear:**	ECG on/off
Illumination mode:	M/NM	**Emergency operating time, h:**	1
Connection:	Push-in terminal, 4x2x2.5mm2		

LIGHTING DATA

Light source and cap, W:	LED	**Light source included:**	yes
CRI (Ra):	80+	**CCT, K:**	6500
SDCM:	3	**Light Distribution:**	Other
Distribution Type:	Omnidirectional	**LED lifetime, h:**	50000/L80B50


TECHNICAL DATA

Net weight, kg:	1.2	**Quantity in package, pcs:**	1
Packaging volume, m3/pcs:	0.0039	**Pallet quantity, pcs:**	256
Dimensions, mm:	315x48x243		

STANDARDS

Operating temperature range, °C:	ta 0...+40	**Protection class IEC:**	I
Ingress protection code:	IP41	**Mechanical impact resistance:**	IK02
Certificates:	CE, UKCA, RoHS	**Warranty:**	2 years

Technical drawing (.jpg)



Note:	*: M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C