

# **ZONDA 3PLED C351 OP • 1019314**



Product:	Zonda 3PLED C351 OP
Order code:	1019314
Family:	Zonda LED
Product group:	Emergency lighting

### GENERAL DATA

**Description:** A surface double-sided LED emergency exit sign

Light distribution type: omnidirectional Optical system: opal polycarbonate diffuser

Housing: polycarbonate

Colour: white

Battery charging time: 24 hours

Battery: NiCd, deep discharge protection

Recognition distance: 30 meters

**Instalation:** On the ceiling or wall. Screw terminal, 3x2x2.5mm2

**Environment** Indoor

Application emergency exit sign

### **ELECTRICAL DATA**

Mains voltage:	220-240V, 50/60Hz	System power*, W:	1	
Power factor:	>0,60	Control gear:	ECG on/off	
Illumination mode:	M/NM	Emergency operating tim	<b>e, h:</b> 3	
Connection:	Push-in terminal, 3x2x2.5mm2			

### LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
CRI (Ra):	80+	CCT, K:	6500
SDCM:	3	Light Distribution:	Other
Distribution Type:	Omnidirectional	LED lifetime, h:	50000/L80B50


## TECHNICAL DATA

Net weight, kg:	1.15	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0035	Pallet quantity, pcs:	256
Dimensions, mm:	325x41x250		

### **STANDARDS**

317 II 1D7 II 1D3			
Operating temperature range, °C:	ta 0+40	Protection class IEC:	II
Ingress protection code:	IP44	Mechanical impact resistance:	IK08
Certificates:	CE, UKCA, RoHS	Warranty:	2 years

Technical drawing (.jpg)



Note:

\*: M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data:  $\pm 10\%$ , values apply to an ambient temperature of 25°C

Date of issue: 2024-05-04 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org