

**PEGASUS H LED1X3350 E830 T830 R40 • 1101061**


Product:	Pegasus H LED1x3350 E830 T830 R40
Order code:	1101061
Family:	Pegasus H LED
Product group:	Spotlights

**GENERAL DATA**

<b>Description:</b>	Recessed mounted adjustable LED spotlight Light distribution type: direct Optical system: faceted aluminium reflector, clear PMMA diffuser Housing: aluminium Colour: white (RAL 9016)
<b>Installation:</b>	In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1.5mm2
<b>Environment</b>	Indoor
<b>Application</b>	retail, public place, showroom, museum, exhibition

**ELECTRICAL DATA**

<b>Mains voltage:</b>	220-240V, 0/50/60Hz	<b>System power*, W:</b>	26.5
<b>Power factor:</b>	0.95	<b>Control gear:</b>	ECG on/off
<b>Integrated sensor:</b>	None	<b>Surge protection (L to N), kV:</b>	1
<b>Surge protection (L/N to PE), kV:</b>	2	<b>Inrush current (Imax/time):</b>	5A/ 50µs
<b>Overvoltage protection:</b>	320V AC, 1h	<b>Connection:</b>	Push-in terminal, 2x1.5mm2

**LIGHTING DATA**

<b>Light source and cap, W:</b>	LED	<b>Light source included:</b>	yes
<b>Luminaire output*, lm(ta+25°C):</b>	3290	<b>System efficacy, lm/W:</b>	124
<b>CRI (Ra):</b>	80+	<b>CCT, K:</b>	3000
<b>SDCM:</b>	3	<b>Light Distribution:</b>	Symmetrical medium beam (31 ...75 )
<b>Distribution Type:</b>	Direct	<b>Beam angle, °:</b>	32
<b>LED lifetime, h:</b>	60000/L80B10	<b>Ripple current (≤120 Hz), %:</b>	≤3


**TECHNICAL DATA**

<b>Net weight, kg:</b>	1.4	<b>Mounting holes/cut-out dimensions, mm:</b>	165x165
<b>Quantity in package, pcs:</b>	1	<b>Packaging volume, m3/pcs:</b>	0.0047
<b>Pallet quantity, pcs:</b>	190		
<b>Dimensions, mm:</b>	175x175x119		


**STANDARDS**

<b>Operating temperature range, °C:</b>	ta 0...+35	<b>Protection class IEC:</b>	II
<b>Ingress protection code:</b>	IP20	<b>Mechanical impact resistance:</b>	IK02
<b>EEC:</b>	D	<b>Certificates:</b>	CE, UKCA, RoHS
<b>Warranty:</b>	3 years (5 years - see warranty)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



**Note:** Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.