

SPICA LED1X2550 D952 T830 LS90X100 • 1101247



Product:	Spica LED1x2550 D952 T830 LS90x100			
Order code:	1101247			
Family:	Spica LED			
Product group	: Spotlights			


GENERAL DATA

Description:	A linear LED track light with various optics designed for the general lighting Optics: 30x90°, 60x100°, 90x100°, asymmetric and double asymmetric light beam Body: steel sheet, white finish, with adaptor		
Instalation:	Surface luminaire is designed to be fixed into 4/6-conductors surface/recessed tracks. Track adaptor (3-phase + N) with phase selector		
Environment	Indoor		
Application	retail, public place, showroom, exhibition		


ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	17.9
Power factor:	>0,95	Control gear:	ECG on/off
Connection:	Track adaptor (3-phase + N) with phase selector		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	2439	System efficacy, Im/W:	136
CRI (Ra):	80+	ССТ, К:	3000
SDCM:	3	Distribution Type:	Direct
LED lifetime, h:	100000/L80B50		
TECHNICAL DATA			
Net weight, kg:	1.7	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0043	Pallet quantity, pcs:	200
Dimensions, mm:	583x80x70		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	I
Ingress protection code:	IP20	Mechanical impact resistance:	IK02
EEC:	A++	Certificates:	CE, RoHS
Warranty:	3 years		
Tochnical drawing (ing)			

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note: Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C

Date of issue: 2024-04-19 NORTHCLIFFE LIGHTING, UAB Raudondvario pl. 101, LT-47184 Kaunas, Lithuania info@northcliffe.org