TETRA A LED1X1650 D985 T830 MPRZ LT92 • 1101716



Product:	Tetra A LED1x1650 D985 T830 MPRZ LT92		
Order code:	1101716		
Family:	Tetra A LED		
Product group: Downlights			


GENERAL DATA

Description:	Recessed mounted LED downlight		
	Light distribution type: direct		
	Optical system: translucent micro-prismatic PMMA diffuser		
	Housing: steel		
	Colour: white (RAL 9003)		
Instalation:	In ceilings with cut-out openings (mounting brackets included).		
	Push-in terminal, 2x1x1.5mm2		
Environment	Indoor		
Application	office, education, corridor, retail, public place, showroom, hotel, bathroom		


ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	14,7
Power factor:	>0,95	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Push-in terminal, 2x1x1.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	1547	System efficacy, Im/W:	105
CRI (Ra):	80+	ССТ, К:	3000
SDCM:	3	Light Distribution:	Symmetrical wide beam (76 125)
Distribution Type:	Direct	Beam angle, °:	91
UGR index:	≤22	LED lifetime, h:	50000/L80B10
TECHNICAL DATA			
Net weight, kg:	1.5	Mounting holes/cut-out dimensions, mm:	245x240
Quantity in package, pcs:	1	Packaging volume, m3/pcs:	0.0057
Pallet quantity, pcs:	150		
Dimensions, mm:	260x260x65		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	II
Ingress protection code:	IP44	Mechanical impact resistance:	IK05
EEC:	E	Certificates:	CE, UKCA, RoHS
Warranty:	3 years (5 years – see warranty Ts and Cs)		
Technical drawing (.ing)			

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-05-03
NORTHCLIFFE LIGHTING, UAB
Raudondvario pl. 101, LT-47184 Kaunas, Lithuania
info@northcliffe.org
www.northcliffe.org