

## BOREAS MM LED1X8800 D351 T740 LS12 • 1020987



Product:	Boreas MM LED1x8800 D351 T740 LS12		
Order code:	1020987		
Family:	Boreas M LED		
Product group:	Floodlights		

## GENERAL DATA

**Description:** Surface mounted LED floodlight

Light distribution type: direct

Optical system: lenses, tempered glass diffuser, impact resistant

Housing: aluminium

Colour: dark grey (RAL 7043)

**Instalation:** On horizontal or vertical surface. Push-in terminal, 3x2x2.5mm2

**Environment** Outdoor

**Application** park, public space, industry, parking area, sports, facade illumination, street


## **ELECTRICAL DATA**

Mains voltage:	220-240V, 50/60Hz	System power*, W:	68.9
Power factor:	>0,95	Control gear:	ECG on/off
Connection:	Push-in terminal, 3x2x2.5mm2		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	8712	System efficacy, lm/W:	126
CRI (Ra):	70+	CCT, K:	4000
SDCM:	3	Light Distribution:	Symmetrical ultra narrow beam $(\leq 15^{\circ})$
Distribution Type:	Direct	Beam angle, °:	12
LED lifetime, h:	100000/L90B10		
TECHNICAL DATA			
Net weight, kg:	5	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0128	Pallet quantity, pcs:	70
Dimensions, mm:	444x353x66		
STANDARDS			
Operating temperature range, °C:	-30+40 C	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	D	Certificates:	CE, RoHS


Technical drawing (.jpg)

3 years

Warranty:



## Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2024-05-11 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org