

## BOREAS MM LED1X12100 D352 T730 LSA1 • 1101573

220-240V, 50/60Hz

444x353x66



Product:	Boreas MM LED1x12100 D352 T730 LSA1			
Order code:	1101573			
Family:	Boreas M LED			
Product group: Floodlights				

#### GENERAL DATA

**Description:** Surface mounted LED floodlight

Light distribution type: direct

Optical system: lenses, tempered glass diffuser, impact resistant

Housing: aluminium

System power\*, W:

Colour: dark grey (RAL 7043)

**Instalation:** On horizontal or vertical surface. Push-in terminal, 3x2x2.5mm2

**Environment** Outdoor

**Application** park, public space, industry, parking area, sports, facade illumination, street

105.8

#### **ELECTRICAL DATA**

Mains voltage:


Power factor:	>0,95	Control gear:	ECG on/off		
Connection:	Push-in terminal, 3x2x2.5mm2				
LIGHTING DATA					
Light source and cap, W:	LED	Light source included:	yes		
Luminaire output*, lm(ta+25°C):	11469	System efficacy, lm/W:	108		
CRI (Ra):	70+	CCT, K:	3000		
SDCM:	3	Light Distribution:	Asymmetrical		
Distribution Type:	Direct	Beam angle, °:	Asymmetrical		
LED lifetime, h:	100000/L90B10				
TECHNICAL DATA					
Net weight, kg:	5	Quantity in package, pcs:	1		
Packaging volume, m3/pcs:	0.0128	Pallet quantity, pcs:	70		

### **STANDARDS**


Dimensions, mm:

Operating temperature range, °C:	-30+40 C	Protection class IEC:	I	
Ingress protection code:	IP65	Mechanical impact resistance:	IK08	
EEC:	E	Certificates:	CE, RoHS	
Warranty:	3 years			

Technical drawing (.jpg)



# Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2024-04-25 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org