

BOREAS MS LED1X6100 D350 T740 LSM1 • 1021035

Product:	Boreas MS LED1x6100 D350 T740 LSM1
Order code:	1021035
Family:	Boreas M LED
Product group:	Floodlights

GENERAL DATA

Description:	Surface mounted LED floodlight Light distribution type: direct Optical system: lenses, tempered glass diffuser, impact resistant Housing: aluminium Colour: dark grey (RAL 7043)
Installation:	On horizontal or vertical surface. Push-in terminal, 3x2x2.5mm2
Environment	Outdoor
Application	park, public space, industry, parking area, sports, facade illumination, street

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	52.9
Power factor:	>0,95	Control gear:	ECG on/off
Connection:	Push-in terminal, 3x2x2.5mm2		

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	5967	System efficacy, lm/W:	113
CRI (Ra):	70+	CCT, K:	4000
SDCM:	3	Light Distribution:	Asymmetrical
Distribution Type:	Direct	Beam angle, °:	Asymmetrical
LED lifetime, h:	100000/L90B10		

TECHNICAL DATA


Net weight, kg:	2.8	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0073	Pallet quantity, pcs:	120
Dimensions, mm:	338x280x60		

STANDARDS

Operating temperature range, °C:	-25...+40 C	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years		
Technical drawing (.jpg)			



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2024-04-20 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org