

BOREAS MB LED1X24200 D355 T740 LSM1 • 1021040

220-240V, 50/60Hz

0.0223

515x420x87



Product:	Boreas MB LED1x24200 D355 T740 LSM1	
Order code:	1021040	
Family:	Boreas M LED	
Product group: Floodlights		

GENERAL DATA

Description: Surface mounted LED floodlight

Light distribution type: direct

Optical system: lenses, tempered glass diffuser, impact resistant

Housing: aluminium

System power*, W:

Pallet quantity, pcs:

Colour: dark grey (RAL 7043)

Instalation: On horizontal or vertical surface. Push-in terminal, 3x2x2.5mm2

Environment Outdoor

Application park, public space, industry, parking area, sports, facade illumination, street

211.6

40

ELECTRICAL DATA

Mains voltage:

Power factor:	>0,95	Control gear:	ECG on/off
Connection:	Push-in terminal, 3x2x2.5mm2		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	23867	System efficacy, lm/W:	113
CRI (Ra):	70+	CCT, K:	4000
SDCM:	3	Light Distribution:	Asymmetrical
Distribution Type:	Direct	Beam angle, °:	Asymmetrical
LED lifetime, h:	100000/L90B10		
TECHNICAL DATA			
Net weight, kg:	7.6	Quantity in package, pcs:	1


STANDARDS

Dimensions, mm:


Operating temperature range, °C:	-30+40 C	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)

Packaging volume, m3/pcs:



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2024-04-18 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org