TUBE M LED2X2000 D044 T830 L45 • 1021154




Product:	Tube M LED2x2000 D044 T830 L45
Order code:	1021154
Family:	Tube M LED
Product group	: Outdoor accent lighting
GENERAL D	ATA
Description:	Surface mounted LED wall washer
	Light distribution type: direct
	Optical system: lenses, tempered glass diffuser, impact resistant
	Housing: aluminium
	Colour: dark grey (RAL7043)
Instalation:	On the wall or ceiling. Screw terminal, 3x1x1.5mm2
Environment	Outdoor
Application	facade illumination

ELECTRICAL DATA


Image not found or type unknown

Mains voltage:	220-240V, 50/60Hz	System power*, W:	38,4
Power factor:	>0,9	Control gear:	ECG on/off
Integrated sensor:	None	Connection:	Screw terminal, 3x1x1.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	3927	System efficacy, Im/W:	102
CRI (Ra):	80+	ССТ, К:	3000
SDCM:	3	Light Distribution:	Symmetrical medium beam (31°75°)
Distribution Type:	Direct	Beam angle, °:	60
LED lifetime, h:	60000/L80B10		
TECHNICAL DATA			
Net weight, kg:	3.2	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0137	Pallet quantity, pcs:	60
Dimensions, mm:	200x155x464		
STANDARDS			
Operating temperature range, °C:	-25+40 C	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	E	Certificates:	CE, RoHS
Warranty:	3 years (5 years – see warranty Ts and Cs)		
T			

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Date of issue: 2024-05-04
NORTHCLIFFE LIGHTING, UAB Raudondvario pl. 101, LT-47184 Kaunas, Lithuania info@northcliffe.org
www.northcliffe.org