

ATLAS M LED1X1500 D455 T830 L45 • 1020484

| | |
|----------------|---------------------------------|
| Product: | Atlas M LED1x1500 D455 T830 L45 |
| Order code: | 1020484 |
| Family: | Atlas M LED |
| Product group: | Outdoor accent lighting |

GENERAL DATA

| | |
|----------------------|---|
| Description: | Ground-mounted LED luminaire Light distribution type: direct Optical system: lens, tempered glass diffuser, impact resistant Housing: aluminum, dark grey (RAL7043) Frame: stainless-steel, brushed |
| Installation: | In the ground. Cable, 1.0m, 3x1.5mm2 |
| Environment | Outdoor |
| Application | public space, facade illumination |

ELECTRICAL DATA

| | | | |
|---------------------------|-------------------|--------------------------|-----------------------|
| Mains voltage: | 220-240V, 50/60Hz | System power*, W: | 13.1 |
| Power factor: | >0,90 | Control gear: | ECG on/off |
| Integrated sensor: | None | Connection: | Cable, 1.0m, 3x1.5mm2 |

LIGHTING DATA

| | | | |
|--|--------------|-------------------------------|--|
| Light source and cap, W: | LED | Light source included: | yes |
| Luminaire output*, lm(ta+25°C): | 1415 | System efficacy, lm/W: | 108 |
| CRI (Ra): | 80+ | CCT, K: | 3000 |
| SDCM: | 3 | Light Distribution: | Symmetrical medium beam (31°...75°) |
| Distribution Type: | Direct | Beam angle, °: | 60 |
| LED lifetime, h: | 40000/L80B50 | | |


TECHNICAL DATA

| | | | |
|----------------------------------|-------------|----------------------------------|----|
| Net weight, kg: | 4.5 | Quantity in package, pcs: | 1 |
| Packaging volume, m3/pcs: | 0.0113 | Pallet quantity, pcs: | 80 |
| Dimensions, mm: | 200x200x235 | | |


STANDARDS

| | | | |
|---|-------------|--|----------|
| Operating temperature range, °C: | -25...+40 C | Protection class IEC: | I |
| Ingress protection code: | IP67 | Mechanical impact resistance: | IK10 |
| EEC: | E | Certificates: | CE, RoHS |
| Warranty: | 3 years | | |

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.