PRODUCT DATA SHEET

NORTHCLIFFE
MAKING LIFE BRIGHTER

AUVA LED1X4250 G094 T730 LSM2 • 1102833



Product:	Auva LED1x4250 G094 T730 LSM2
Order code:	1102833
Family:	Auva LED
Product group:	Park and street luminaires

GENERAL DATA

Description:	Pole-mounted LED street luminaire Light distribution: direct Optical system: lenses, tempered glass diffuser, impact resistant Housing: aluminum Colour: light grey (RAL7035)
Instalation:	With two screws on Ø60mm horizontal or vertical pole, on the wall (mounting bracket to be ordered separately). Adjustable installation angles: on horizontal pole: +/- 15 degrees, on vertical pole: +/- 15 degrees. Screw terminal, 3x1x2.5mm2
Environment	Outdoor
Application	public space, parking area, street

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	**System power*, W:**	34.2
Power factor:	>0,95	**Control gear:**	ECG on/off
Integrated sensor:	None	**Connection:**	Screw terminal, 3x1x2.5mm2

LIGHTING DATA

Light source and cap, W:	LED	**Light source included:**	yes
Luminaire output*, lm(ta+25°C):	4267	**System efficacy, lm/W:**	125
CRI (Ra):	70+	**CCT, K:**	3000
SDCM:	3	**Light Distribution:**	Other
Distribution Type:	Direct	**Beam angle, °:**	Asymmetrical
LED lifetime, h:	100000/L90B10		


TECHNICAL DATA

Net weight, kg:	5	**Quantity in package, pcs:**	1
Packaging volume, m3/pcs:	0.0159	**Pallet quantity, pcs:**	70
Dimensions, mm:	525x250x102		


STANDARDS

Operating temperature range, °C:	ta -25...+40	**Protection class IEC:**	I
Ingress protection code:	IP66	**Mechanical impact resistance:**	IK09
EEC:	D	**Certificates:**	CE, RoHS
Warranty:	3 years		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:	Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification