

SERPENS S LED1X850 G367 T840 OP LO2 SB • 1105668



Product:	Serpens S LED1x850 G367 T840 OP LO2 SB
Order code:	1105668
Family:	Serpens S LED
Product group:	Aluminium profile luminaires

GENERAL DATA

Description:	Recessed mounted slim profile LED luminaire for in-line connection Light distribution type: direct Optical system: opal polycarbonate diffuser Housing: aluminium	
To a factor to the contract of	Colour: white (RAL9003S)	
Instalation:	In ceilings with cut-out openings (mounting brackets included) with L/LL option is designed for in-line connection. Push-in terminal, 3x2x2.5mm2	
Environment	Indoor	
Application	office, education, corridor, retail, public place, hotel	

ELECTRICAL DATA			
Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	9.6
Power factor:	0.95	Control gear:	ECG on/off
Integrated sensor:	None	Surge protection (L to N), kV:	2
Surge protection (L/N to PE), kV:	4	Inrush current (Imax/time):	5A/ 50μs
Connection:	Push-in terminal, 3x2x2.5mm2		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	832	System efficacy, lm/W:	86
CRI (Ra):	80+	CCT, K:	4000
SDCM:	3	Light Distribution:	Wide-wide beam (C0-C180 plane 76125 , C90-C270 plane 76125)
Distribution Type:	Direct	Beam angle, °:	109x109
LED lifetime, h:	50000/L80B10	Ripple current (≤120 Hz), %:	≤3
TECHNICAL DATA			
Net weight, kg:	1.5	Mounting holes/cut-out dimensions, mm:	583x45
Quantity in package, pcs:	1	Packaging volume, m3/pcs:	0.0034
Pallet quantity, pcs:	250		
Dimensions, mm:	595x55x75		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	I
Ingress protection code:	IP40	Mechanical impact	IK05

resistance:


Glow wire test, °C: 650 EEC: F
Certificates: CE, UKCA, RoHS Warranty: 3 years (5 years - see warranty Ts and Cs)

Technical drawing (.jpg)





Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-05-04 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org