

SERPENS S LED1X2450 G581 T840 OP LO1 SB • 1107485




Product:	Serpens S LED1x2450 G581 T840 OP LO1 SB	
Order code:	1107485	
Family:	Serpens S LED	
Product group: Aluminium profile luminaires		

GENERAL DATA


Recessed mounted slim profile LED luminaire for in-line connection Light distribution type: direct Optical system: opal polycarbonate diffuser Housing: aluminium Colour: white (RAL9003S)		
In ceilings with cut-out openings (mounting brackets included), with L/LL option is designed for in-line connection. Push-in terminal, 3x2x2.5mm2		
Indoor		
office, education, corridor, retail, public place, hotel		

ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	23.5
Power factor:	0.95	Control gear:	ECG on/off
Integrated sensor:	None	Surge protection (L to N), kV:	1
Surge protection (L/N to PE), kV:	2	Inrush current (Imax/time):	22A/ 136µs
Overvoltage protection:	320V AC, 1h	Connection:	Push-in terminal, 3x2x2.5mm2
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	2441	System efficacy, Im/W:	104
CRI (Ra):	80+	ССТ, К:	4000
SDCM:	3	Light Distribution:	Wide-wide beam (C0-C180 plane 76125 , C90-C270 plane 76 125)
Distribution Type:	Direct	Beam angle, °:	109x109
LED lifetime, h:	50000/L80B10	Ripple current (≤120 Hz), %:	≤1
TECHNICAL DATA			
Net weight, kg:	4.6	Mounting holes/cut-out dimensions, mm:	2263x45
Quantity in package, pcs:	1	Packaging volume, m3/pcs:	0.0071
Pallet quantity, pcs:	84		
Dimensions, mm:	2275x55x75		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	1
Ingress protection code:	IP40	Mechanical impact resistance:	IK05



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-05-05 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org www.northcliffe.org