## LODOS S LED1X1800 E968 T840 DPRZ LT80 • 1102765



Image not found or type unknown

| Development of the second | Conference of a second address to a local second |
|---------------------------|--|
| Family:                   | Lodos S LED                                      |
| Order code:               | 1102765  |
| Product:                  | Lodos S LED1x1800 E968 T840 DPRZ LT80            |

Product group: Surface and suspended luminaires


### GENERAL DATA

| Description: | Surface mounted decorative LED luminaire<br>Light distribution type: direct<br>Optical system: matt micro-prismatic PMMA diffuser, UGR<19<br>Housing: steel<br>Colour: white (RAL9003) |  |  |
|--------------|--|--|--|
| Instalation: | On the ceiling or suspended (accessories to be ordered separately). Push-in terminal, 3x2x2.5mm2   |  |  |
| Environment  | Indoor   |  |  |
| Application  | office, education, retail, public place  |  |  |
|              |  |  |  |


### ELECTRICAL DATA

| Mains voltage:                      | 220-240V, 0/50/60Hz                           | System power*, W:                    | 15,9                               |
|-------------------------------------|---|--------------------------------------|------------------------------------|
| Power factor:                       | >0,95   | Control gear:                        | ECG on/off                         |
| Surge protection (L to N), kV:      | 1   | Surge protection (L/N to PE),<br>kV: | 2                                  |
| Inrush current (Imax/time):         | 5A 50µsec                                     | Overvoltage protection:              | 320V AC, 1h                        |
| Connection:                         | Push-in terminal, 3x2x2.5mm2                  |                                      |                                    |
| LIGHTING DATA                       |   |                                      |                                    |
| Light source and cap, W:            | LED   | Light source included:               | yes                                |
| Luminaire output*,<br>lm(ta+25°C):  | 1780  | System efficacy, Im/W:               | 112                                |
| CRI (Ra):                           | 80+   | ССТ, К:                              | 4000                               |
| SDCM:                               | 3   | Light Distribution:                  | Symmetrical wide beam (76<br>125 ) |
| Distribution Type:                  | Direct  | Beam angle, °:                       | 92                                 |
| UGR index:                          | ≤19   | LED lifetime, h:                     | 50000/L80B10                       |
| Ripple current (≤120 Hz), %:        | ≤3  |                                      |                                    |
| TECHNICAL DATA                      |   |                                      |                                    |
| Net weight, kg:                     | 2,5   | Quantity in package, pcs:            | 1                                  |
| Packaging volume, m3/pcs:           | 0.0134  | Pallet quantity, pcs:                | 96                                 |
| Dimensions, mm:                     | 300x300x100                                   |                                      |                                    |
| STANDARDS                           |   |                                      |                                    |
| Operating temperature<br>range, °C: | ta 0+35                                       | Protection class IEC:                | Ι                                  |
| Ingress protection code:            | IP40  | Mechanical impact<br>resistance:     | IK02                               |
| EEC:                                | E   | Certificates:                        | CE, UKCA, RoHS                     |
| Warranty:                           | 3 years (5 years – see warranty<br>Ts and Cs) |                                      |                                    |

### Technical drawing (.jpg)



# Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-04-20 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org