

**LODOS S LED1X9350 E974 T840 DPRZ LT80 • 1102771**


Image not found or type unknown



Product:	Lodos S LED1x9350 E974 T840 DPRZ LT80
Order code:	1102771
Family:	Lodos S LED
Product group:	Surface and suspended luminaires

**GENERAL DATA**

<b>Description:</b>	Surface mounted decorative LED luminaire Light distribution type: direct Optical system: matt micro-prismatic PMMA diffuser, UGR<19 Housing: steel Colour: white (RAL9003)
<b>Installation:</b>	On the ceiling or suspended (accessories to be ordered separately). Push-in terminal, 3x2x2.5mm2
<b>Environment</b>	Indoor
<b>Application</b>	office, education, retail, public place

**ELECTRICAL DATA**

<b>Mains voltage:</b>	220-240V, 0/50/60Hz	<b>System power*, W:</b>	73
<b>Power factor:</b>	>0,95	<b>Control gear:</b>	ECG on/off
<b>Surge protection (L to N), kV:</b>	1	<b>Surge protection (L/N to PE), kV:</b>	2
<b>Inrush current (Imax/time):</b>	39A/ 166µs	<b>Overvoltage protection:</b>	320V AC, 1h
<b>Connection:</b>	Push-in terminal, 3x2x2.5mm2		

**LIGHTING DATA**

<b>Light source and cap, W:</b>	LED	<b>Light source included:</b>	yes
<b>Luminaire output*, lm(ta+25°C):</b>	9330	<b>System efficacy, lm/W:</b>	128
<b>CRI (Ra):</b>	80+	<b>CCT, K:</b>	4000
<b>SDCM:</b>	3	<b>Light Distribution:</b>	Symmetrical wide beam (76 ...125 )
<b>Distribution Type:</b>	Direct	<b>Beam angle, °:</b>	92
<b>UGR index:</b>	≤19	<b>LED lifetime, h:</b>	50000/L80B10
<b>Ripple current (≤120 Hz), %:</b>	≤2		


**TECHNICAL DATA**

<b>Net weight, kg:</b>	14,1	<b>Quantity in package, pcs:</b>	1
<b>Packaging volume, m3/pcs:</b>	0.134	<b>Pallet quantity, pcs:</b>	10
<b>Dimensions, mm:</b>	900x900x114		


**STANDARDS**

<b>Operating temperature range, °C:</b>	ta 0...+35	<b>Protection class IEC:</b>	I
<b>Ingress protection code:</b>	IP40	<b>Mechanical impact resistance:</b>	IK02
<b>EEC:</b>	D	<b>Certificates:</b>	CE, UKCA, RoHS
<b>Warranty:</b>	3 years (5 years – see warranty Ts and Cs)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



**Note:** Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.