

SEGIN LED1X6500 E943 T730 LSM1 • 1107516


Product:	Segin LED1x6500 E943 T730 LSM1
Order code:	1107516
Family:	Segin LED
Product group:	Park and street luminaires

GENERAL DATA

Description:	Pole-mounted LED park luminaire Light distribution type: direct Optical system: lenses, tempered glass diffuser, impact resistant Housing: aluminium Colour: black grey (RAL7021)
Installation:	With three screws on pole Ø60mm. Push-in terminal, 3x2x2.5mm2
Environment	Outdoor
Application	park, public space, parking area

ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	51
Power factor:	0.95	Control gear:	ECG on/off
Integrated sensor:	None	Surge protection (L to N), kV:	2
Surge protection (L/N to PE), kV:	2	Inrush current (Imax/time):	5A/ 50µs
Connection:	Push-in terminal, 3x2x2.5mm2		

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	6250	System efficacy, lm/W:	123
CRI (Ra):	70+	CCT, K:	3000
SDCM:	3	Light Distribution:	Other
Distribution Type:	Direct	LED lifetime, h:	100000/L90B10


TECHNICAL DATA

Net weight, kg:	8.2	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.1599	Pallet quantity, pcs:	9
Dimensions, mm:	425x425x816		


STANDARDS

Operating temperature range, °C:	ta -25...+40	Protection class IEC:	I
Ingress protection code:	IP65	Mechanical impact resistance:	IK08
EEC:	D	Certificates:	CE, UKCA, RoHS
Warranty:	3 years (5 years – see warranty Ts and Cs)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification