

BOOTES C LED1x5350 G561 T830 DPRZ LT80 • 1108465


Image not found or type unknown



Product:	Bootes C LED1x5350 G561 T830 DPRZ LT80
Order code:	1108465
Family:	Bootes C LED
Product group:	Surface and suspended luminaires

GENERAL DATA

Description:	Surface decorative LED luminaire Light distribution type: direct/indirect Optical system: matt micro-prismatic PMMA diffuser, UGR≤19 Housing: steel Colour: grey (RAL9006)
Installation:	On the ceiling, on the wall or suspended (accessories be ordered separately). Push-in terminal, 3x2x2.5mm2
Environment	Indoor
Application	office, education, retail, public place

ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	36.4
Power factor:	0.97	Control gear:	ECG on/off
Integrated sensor:	None	Surge protection (L to N), kV:	1
Surge protection (L/N to PE), kV:	2	Inrush current (Imax/time):	23A/ 140µs
Overvoltage protection:	330V AC, 1h	Connection:	Push-in terminal, 3x2x2.5mm2

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	4598	System efficacy, lm/W:	126
CRI (Ra):	80+	CCT, K:	3000
SDCM:	3	Light Distribution:	Symmetrical wide beam (76 ...125)
Distribution Type:	Direct/indirect	Beam angle, °:	92
UGR index:	≤19	LED lifetime, h:	50000/L80B10
Ripple current (≤120 Hz), %:	≤1		


TECHNICAL DATA

Net weight, kg:	4.8	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0196	Pallet quantity, pcs:	40
Dimensions, mm:	450x450x92		


STANDARDS

Operating temperature range, °C:	ta 0...+35	Protection class IEC:	I
Ingress protection code:	IP20	Mechanical impact resistance:	IK02
EEC:	D	Certificates:	CE, UKCA, RoHS
Warranty:	3 years (5 years - see warranty Ts and Cs)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note: Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.