

CORONA C LED1X4800 D068 T830 OP LT80 • 1020032

Product:	Corona C LED1x4800 D068 T830 OP LT80
Order code:	1020032
Family:	Corona C LED
Product group:	Recessed luminaires

GENERAL DATA

Description:	Recessed mounted decorative LED luminaire Light distribution type: direct Optical system: low glare matt micro-prismatic (DPRZ LT80) or high transmission opal (OP LT80) diffuser, PMMA Housing: steel Colour: white (RAL9003)
Installation:	In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting frame to be ordered separately). Push-in terminal, 2x1.5mm2
Environment	Indoor
Application	office, education, corridor, retail, public place

ELECTRICAL DATA

Mains voltage:	220-240V, 50/60Hz	System power*, W:	38.5
Power factor:	>0,95	Control gear:	ECG on/off
Inrush current (Imax/time):	5A 50µsec	Connection:	Push-in terminal, 2x1.5mm2

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	4554	System efficacy, lm/W:	118
CRI (Ra):	80+	CCT, K:	3000
Light Distribution:	Symmetrical wide beam (76 ...125)	Distribution Type:	Direct
Beam angle, °:	107	LED lifetime, h:	100000/L80B50
Ripple current (≤120 Hz), %:	±3		


TECHNICAL DATA

Net weight, kg:	3.1	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.0298	Pallet quantity, pcs:	30
Dimensions, mm:	595x595x70		


STANDARDS

Operating temperature range, °C:	ta 0...+35	Protection class IEC:	II
Ingress protection code:	IP40/20	Mechanical impact resistance:	IK05
EEC:	D	Certificates:	CE, UKCA, RoHS
Warranty:	3 years (5 years – see warranty Ts and Cs)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note: Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.