


CALIMA U LED1X4450 H146 T830 DPRZ LT80 • 1107908





Product:	Calima U LED1x4450 H146 T830 DPRZ LT80
Order code:	1107908
Family:	Calima U LED
Product group:	Surface and suspended luminaires

GENERAL DATA

Description:	Suspended LED luminaire, basic version Light distribution type: direct (direct/indirect LG3 version) Optical system: matt micro-prismatic PMMA diffuser, low glare Housing: steel Colour: white (RAL9003)		
Instalation:	Suspended (accessories to be ordered separately), with L/LL option is designed for in-line connection. Push-in terminal, 3x2x2.5mm2		
Environment	Indoor		
Application	office, education, retail, public place		

IK05

CE, RoHS

ELECTRICAL DATA

Ingress protection code:

EEC:

ELECTRICAL DATA			
Mains voltage:	220-240V, 50/60Hz	System power*, W:	31.8
Power factor:	>0,95	Control gear:	ECG on/off
Integrated sensor:	None	Surge protection (L to N), kV:	1
Surge protection (L/N to PE), kV:	2	Inrush current (Imax/time):	5.5A/ 20μs
Connection:	Push-in terminal, 3x2x2.5mm2		
LIGHTING DATA			
Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	4220	System efficacy, lm/W:	133
CRI (Ra):	80+	сст, к:	3000
SDCM:	3	Light Distribution:	Wide-wide beam (C0-C180 plane 75125 , C90-C270 plane 75125)
Distribution Type:	Direct	Beam angle, °:	89x90
UGR index:	≤19	LED lifetime, h:	50000/L80B10
Ripple current (≤120 Hz), %:	≤3		
TECHNICAL DATA			
Net weight, kg:	5.1	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.014	Pallet quantity, pcs:	80
Dimensions, mm:	1495x175x40		
STANDARDS			
Operating temperature range, °C:	ta 0+35	Protection class IEC:	I


Mechanical impact resistance:


Certificates:

IP40


D







Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-05-03 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org