

LODOS S LED1X13450 E982 T840 OP LT80 • 1108670

Image not found or type unknown



Product:	Lodos S LED1x13450 E982 T840 OP LT80
Order code:	1108670
Family:	Lodos S LED
Product group:	Surface and suspended luminaires

GENERAL DATA

Description:	Surface mounted decorative LED luminaire Light distribution type: direct Optical system: opal PMMA diffuser Housing: steel Colour: white (RAL9003)
Installation:	On the ceiling or suspended (accessories to be ordered separately). Push-in terminal, 3x2x2.5mm2
Environment	Indoor
Application	office, education, retail, public place

ELECTRICAL DATA

Mains voltage:	220-240V, 0/50/60Hz	System power*, W:	94,1
Power factor:	>0,95	Control gear:	ECG on/off
Surge protection (L to N), kV:	1	Surge protection (L/N to PE), kV:	2
Inrush current (Imax/time):	41A/ 221μs	Overvoltage protection:	320V AC, 1h
Connection:	Push-in terminal, 3x2x2.5mm2		

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	13435	System efficacy, lm/W:	143
CRI (Ra):	80+	CCT, K:	4000
SDCM:	3	Light Distribution:	Symmetrical wide beam (76 ...125)
Distribution Type:	Direct	Beam angle, °:	107
UGR index:	≤22	LED lifetime, h:	50000/L80B10
Ripple current (≤120 Hz), %:	≤2		


TECHNICAL DATA

Net weight, kg:	14,1	Quantity in package, pcs:	1
Packaging volume, m3/pcs:	0.134	Pallet quantity, pcs:	10
Dimensions, mm:	900x900x114		


STANDARDS

Operating temperature range, °C:	ta 0...+35	Protection class IEC:	I
Ingress protection code:	IP40	Mechanical impact resistance:	IK02
EEC:	C	Certificates:	CE, UKCA, RoHS
Warranty:	3 years (5 years – see warranty Ts and Cs)		

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note: Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.