

## MALL LED1X6600 E966 T840 L75 LO5 LL • 1103235



Product: Mall LED1x6600 E966 T840 L75 LO5 LL Order code: 1103235 Family: Mall LED Product group: Continuous line and batten luminaires

## GENERAL DATA

| Description: | Suspended continuous line LED luminaire Light distribution: direct Optical system: lenses Housing: steel Colour: white (RAL 9003)  Suspended (brackets and I-join kit included with each luminaire). Through wired, 5x1.5mm2, two 5-pole plug and socket connectors |  |
|--------------|---|--|
| Instalation: |   |  |
| Environment  | Indoor  |  |
| Application  | retail, public place, hall  |  |

| ELECTRICAL DATA                    |                     |                                |  |
|------------------------------------|---------------------|--------------------------------|--|
| Mains voltage:                     | 220-240V, 0/50/60Hz | System power*, W:              | 35.5   |
| Power factor:                      | 0.98                | Control gear:                  | ECG on/off   |
| Integrated sensor:                 | None                | Surge protection (L to N), kV: | 1  |
| Surge protection (L/N to PE), kV:  | 2                   | Inrush current (Imax/time):    | 33A/ 162µs   |
| Overvoltage protection:            | 330V AC, 1h         | Connection:                    | Through wired, 5x1.5mm2, two 5-pole plug and socket connectors |
| LIGHTING DATA                      |                     |                                |  |
| Light source and cap, W:           | LED                 | Light source included:         | yes  |
| Luminaire output*,<br>lm(ta+25°C): | 6567                | System efficacy, lm/W:         | 185  |
| CRI (Ra):                          | 80+                 | сст, к:                        | 4000   |
|                                    |                     |                                |  |

| CRI (Ra):          | +08    | сст, к:             | 4000                             |
|--------------------|--------|---------------------|----------------------------------|
| SDCM:              | 3      | Light Distribution: | Symmetrical medium beam (31°75°) |
| Distribution Type: | Direct | Beam angle, °:      | 72                               |
| UGR index:         | <22    | LED lifetime. h:    | 100000/I 80B10                   |

Ripple current (≤120 Hz), %:

## TECHNICAL DATA

| Net weight, kg:           | 3.2        | Quantity in package, pcs: | 1   |
|---------------------------|------------|---------------------------|-----|
| Packaging volume, m3/pcs: | 0.0046     | Pallet quantity, pcs:     | 128 |
| Dimensions, mm:           | 1133x65x60 |                           |     |

## **STANDARDS**


| Operating temperature range, °C: | ta 0+40 | Protection class IEC:         | 1    |
|----------------------------------|---------|-------------------------------|------|
| Ingress protection code:         | IP20    | Mechanical impact resistance: | IK05 |
|                                  |         |                               |      |


EEC: Α **Certificates:** CE, UKCA, RoHS

Warranty:

3 years (5 years - see warranty Ts and Cs)


## Technical drawing (.jpg)







# Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data:  $\pm 10\%$ . Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Date of issue: 2024-04-30 ■ NORTHCLIFFE LIGHTING, UAB ■ Raudondvario pl. 101, LT-47184 Kaunas, Lithuania ■ info@northcliffe.org ■ www.northcliffe.org