

**HERMETIC R LED3X2200 D156 T830 OP LT80 • 1100940**


Product:	Hermetic R LED3x2200 D156 T830 OP LT80
Order code:	1100940
Family:	Hermetic R LED
Product group:	Waterproof and cleanroom luminaires

**GENERAL DATA**

<b>Description:</b>	Recessed mounted cleanroom LED luminaire Light distribution type: direct Optical system: opal acrylic diffuser, good chemical resistance Housing: steel Colour: white (RAL9003)
<b>Installation:</b>	In modular suspended ceilings (600/625), in ceilings with cut-out openings (mounting brackets to be ordered separately). Push-in terminal, 3x2x2.5mm <sup>2</sup>
<b>Environment</b>	Indoor
<b>Application</b>	industry, healthcare, laboratory

**ELECTRICAL DATA**

<b>Mains voltage:</b>	220-240V, 0/50/60Hz	<b>System power*, W:</b>	49.4
<b>Power factor:</b>	>0.95	<b>Control gear:</b>	ECG on/off
<b>Integrated sensor:</b>	None	<b>Surge protection (L to N), kV:</b>	1
<b>Surge protection (L/N to PE), kV:</b>	2	<b>Inrush current (I<sub>max</sub>/time):</b>	33A/ 162μs
<b>Overvoltage protection:</b>	320V AC, 1h	<b>Connection:</b>	Push-in terminal, 3x2x2.5mm <sup>2</sup>

**LIGHTING DATA**

<b>Light source and cap, W:</b>	LED	<b>Light source included:</b>	yes
<b>Luminaire output*, lm(ta+25°C):</b>	6303	<b>System efficacy, lm/W:</b>	127
<b>CRI (Ra):</b>	80+	<b>CCT, K:</b>	3000
<b>SDCM:</b>	3	<b>Light Distribution:</b>	Wide-wide beam (C0-C180 plane 76 ...125 , C90-C270 plane 76 ...125 )
<b>Distribution Type:</b>	Direct	<b>Beam angle, °:</b>	106x106
<b>UGR index:</b>	≤22	<b>LED lifetime, h:</b>	100000/L80B10
<b>Ripple current (≤120 Hz), %:</b>	≤1		

**TECHNICAL DATA**


<b>Net weight, kg:</b>	9	<b>Quantity in package, pcs:</b>	1
<b>Packaging volume, m3/pcs:</b>	0.0698	<b>Pallet quantity, pcs:</b>	10
<b>Dimensions, mm:</b>	1195x595x85		

**STANDARDS**


<b>Operating temperature range, °C:</b>	ta -10...+35	<b>Protection class IEC:</b>	I
<b>Ingress protection code:</b>	IP65	<b>Mechanical impact resistance:</b>	IK05
<b>EEC:</b>	D	<b>Certificates:</b>	CE, UKCA, RoHS

Warranty:	3 years (5 years – see warranty Ts and Cs)
-----------	---

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:	Tolerance range for optical and electrical data: $\pm 10\%$ . Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.
-------	---