

ARA R 3PLED C377 LER IP65 AUT • 1103345

Product:	Ara R 3PLED C377 LER IP65 AUT
Order code:	1103345
Family:	Ara R LED
Product group:	Emergency lighting

GENERAL DATA

Description:	Recessed mounted LED emergency escape luminaire Light distribution type: direct Optical system: lenses Housing: polycarbonate Colour: white Battery charging time: 12 hours Battery: LiFePO4, deep discharge protection
Installation:	In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 3x2x2.5mm2. Electronic gear and battery package installed in a separate box
Environment	Indoor
Application	escape route lighting

ELECTRICAL DATA

Mains voltage:	220-240V, 50-60Hz	System power*, W:	6
Power factor:	>0,60	Control gear:	ECG on/off
Illumination mode:	M/NM	Emergency operating time, h:	3
Connection:	Push-in terminal, 3x2x2.5mm2		

LIGHTING DATA

Light source and cap, W:	LED	Light source included:	yes
Luminaire output*, lm(ta+25°C):	785	CRI (Ra):	80+
CCT, K:	6000	SDCM:	3
Light Distribution:	Narrow-wide beam (C0-C180 plane ≤ 30°, C90-C270 plane 76°...125°)	Distribution Type:	Direct
Beam angle, °:	24x159	LED lifetime, h:	70000/L80B10


TECHNICAL DATA

Net weight, kg:	1.1	Mounting holes/cut-out dimensions, mm:	d83
Quantity in package, pcs:	1	Packaging volume, m3/pcs:	0.0004
Pallet quantity, pcs:	560		
Dimensions, mm:	100x100x37		


STANDARDS

Operating temperature range, °C:	ta 0...+40	Protection class IEC:	II
Ingress protection code:	IP65/20	Mechanical impact resistance:	IK08
Certificates:	CE, UKCA, RoHS	Warranty:	2 years

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

*: M-maintained (with an option of connecting as non-maintained), NM- non-maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: $\pm 10\%$, values apply to an ambient temperature of 25°C. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.