

NORTE L LED1X42300 D585 T830 ALU L75 SPORT • 1112119


| | |
|----------------|--|
| Product: | Norte L LED1x42300 D585 T830 ALU L75 SPORT |
| Order code: | 1112119 |
| Family: | Norte L LED SPORT |
| Product group: | Highbays |

GENERAL DATA

| | |
|----------------------|---|
| Description: | Surface mounted high-bay LED luminaire Light distribution type: direct Optical system: lenses, silicone rubber gasket, impact resistance Housing: aluminium Colour: white (RAL9003) |
| Installation: | On the ceiling or wall. Push-in terminal, 5x2x2.5mm2 |
| Environment | Indoor |
| Application | industry, warehouse, hall, sports, transport terminal |

ELECTRICAL DATA

| | | | |
|-----------------------|------------------------------|--------------------------|------------|
| Mains voltage: | 220-240V, 50/60Hz | System power*, W: | 243.5 |
| Power factor: | >0,95 | Control gear: | ECG on/off |
| Connection: | Push-in terminal, 5x2x2.5mm2 | | |

LIGHTING DATA

| | | | |
|--|--------|-------------------------------|--|
| Light source and cap, W: | LED | Light source included: | yes |
| Luminaire output*, lm(ta+25°C): | 34573 | System efficacy, lm/W: | 142 |
| CRI (Ra): | 80+ | CCT, K: | 3000 |
| SDCM: | 3 | Light Distribution: | Symmetrical medium beam (31°...75°) |
| Distribution Type: | Direct | Beam angle, °: | 72 |
| UGR index: | ≤22 | LED lifetime, h: | 100000/L80B10 |


TECHNICAL DATA

| | | | |
|----------------------------------|------------|----------------------------------|----|
| Net weight, kg: | 6.5 | Quantity in package, pcs: | 1 |
| Packaging volume, m3/pcs: | 0.0351 | Pallet quantity, pcs: | 20 |
| Dimensions, mm: | 945x343x93 | | |


STANDARDS

| | | | |
|---|----------------|--|---|
| Operating temperature range, °C: | -20...+35 C | Protection class IEC: | I |
| Ingress protection code: | IP65 | Mechanical impact resistance: | IK10 |
| Protection symbol: | D | EEC: | C |
| Certificates: | CE, UKCA, RoHS | Warranty: | 3 years (5 years - see warranty Ts and Cs) |

Technical drawing (.jpg)



Light distribution curve (.jpg)



Note:

Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25 C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification. Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.