


LEPORIS U LED

Emergency Lighting



Images for the product family and options:



Description:

Suspended double-sided LED emergency exit sign
 Light distribution type: omnidirectional
 Optical system: clear PMMA diffuser
 Housing: polycarbonate
 Colour: white
 Battery charging time: 24 hours (12 hours optional: AUT)
 Battery: NiCd (LiFePO4 optional: AUT), deep discharge protection
 Recognition distance: 30 meters

General data:

Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 70000/L80B10
 SDCM: 3
 Protection class IEC: II
 Ingress protection code: IP40
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta 0...+40 (CEBLED, CLV: ta 0...+50)

Installation:

On to the ceiling. Push-in terminal, 3x2x2.5mm² (CEBLED, CLV: Push-in terminal, 2x2x2.5mm²)

Environment:

Indoor

Application:

Emergency exit sign



Supplied with universal sticker kit.

Product	Length, mm	Width, mm	Height, mm	Illumination mode	Emergency operating time, h	Power in emergency mode, W*	CRI *	CCT*, K	Weight, kg
Leporis U 1PLED G076	224	72	337	M/NM	1	1	80+	6000	1,4
Leporis U 3PLED G077	224	72	337	M/NM	3	1	80+	6000	1,4
Leporis U 1PLED G076 AUT	224	72	337	M/NM	1	1	80+	6000	1,4
Leporis U 3PLED G077 AUT	224	72	337	M/NM	3	1	80+	6000	1,4
Leporis U CEBLED G078	224	72	337	CEB	x	1	80+	6000	1,5
Leporis U 1PLED G076 EMS	224	72	337	EMS M/NM	1	1	80+	6000	1,4
Leporis U 3PLED G077 EMS	224	72	337	EMS M/NM	3	1	80+	6000	1,4
Leporis U 1PLED G076 DALI	224	72	337	DALI M/NM	1	1	80+	6000	1,4
Leporis U 3PLED G077 DALI	224	72	337	DALI M/NM	3	1	80+	6000	1,4
Leporis U CLV U54	224	72	337	CLV	x	1	80+	6000	1,5
Leporis U 1PLED G085 2CLR AUT	224	72	337	M/NM	1	3	80+	6000	1,4
Leporis U 3PLED G086 2CLR AUT	224	72	337	M/NM	3	3	80+	6000	1,4
Leporis U CEBLED G087 2CLR	224	72	337	CEB	x	3	80+	6000	1,5
Leporis U 1PLED G085 2CLR EMS	224	72	337	EMS M/NM	1	3	80+	6000	1,4
Leporis U 3PLED G086 2CLR EMS	224	72	337	EMS M/NM	3	3	80+	6000	1,4
Leporis U 1PLED G085 2CLR DALI	224	72	337	DALI M/NM	1	3	80+	6000	1,4
Leporis U 3PLED G086 2CLR DALI	224	72	337	DALI M/NM	3	3	80+	6000	1,4
Leporis U CLV U55 2CLR	224	72	337	CLV	x	3	80+	6000	1,5

*M-maintained (with an option of connecting as non-maintained), NM- non-maintained, CEB maintained, DALI NM- non-maintained, DALI maintained, EMS NM- non-maintained, EMS maintained, CLV maintained, system power and output indicates data in emergency mode, tolerance range for optical and electrical data: ±10%, values apply to an ambient temperature of 25°C

*Photos are for illustrational purposes only. The exact appearance of the product may vary depending on the monitor settings, options selected and other factors.

Available options:

DALI

**note - DALI option is applicable for models: G076, G077*

TEST

Manual test button

AUT

Autonomous testing system

CEB

Fitting to central battery system

CLV

EMS

LGREY

BLACK

Fitting to low voltage central battery system CEBLV

Fitting to emergency monitoring system

Light grey thermoplastic body

Black thermoplastic body