



SIGNUS LED

Park and Street Luminaires



Description:	Pole-mounted LED park luminaire Light distribution type: direct Optical system: frosted polycarbonate diffuser, impact resistant Housing: aluminium Colour: dark grey (RAL7043)
General data:	Mains voltage: 220-240V, 50/60Hz LED lifetime, h: 50000/L90B50 SDCM: 3 Protection class IEC: I (II optional) Ingress protection code: IP65 Mechanical impact resistance: IK08 Operating temperature range, °C: ta -25...+40
Installation:	With three screws on poles Ø60mm. Cable, 3.0m, 3x0.75mm ²
Environment:	Outdoor
Application:	Park, public space



Photocell PCA switches lighting fixtures ON or OFF, at the same time it can be mounted into IP protected light fitting serving as a standalone solution. The built-in photo-sensor records the brightness of the surroundings and switches the connected lighting fixtures on at dusk and of again at dawn. Technical data: IP65- dust and waterproof, 35 lux, 1:05 ratio. For more information see the option list.


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Signus LED1x2700 G663 T830	420	420	420	2536	18,0	141	80+	3000	4,90
Signus LED1x3650 G664 T830	420	420	420	3455	25,2	137	80+	3000	4,90
Signus LED1x4550 G665 T830	420	420	420	4318	32,9	131	80+	3000	4,90
Signus LED1x5200 G666 T830	420	420	420	4962	39,0	127	80+	3000	4,90
Signus LED1x2700 G663 T840	420	420	420	2655	18,0	147	80+	4000	4,90
Signus LED1x3650 G664 T840	420	420	420	3617	25,2	144	80+	4000	4,90
Signus LED1x4550 G665 T840	420	420	420	4521	32,9	137	80+	4000	4,90
Signus LED1x5200 G666 T840	420	420	420	5195	39,0	133	80+	4000	4,90

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming	RAL	RAL colour
PCA	Photocell 20mm miniature type, IP65, 35 lux; 1:05 ratio	T830	Colour temperature 3000K, CRI 80+
II	Electric Shock protection class II	T840	Colour temperature 4000K, CRI 80+

STANDARD



Applications:

